

	SANY SAFE L	SANY SAFE XL
Cover volumes	From 20 m ³ to 300 m ³	From 100 m ³ to 600 m ³
Tanks available	5 L - 10 L - 25 L	
Autonomy days of sanitization	It depends on: intensity, frequency, volume of the environment, tank capacity (8 months with: light intensity / 1 day of the week / 100 m ³ / 25 L)	
Sanitization efficiency Once a day	low intensity: workplaces with only the presence of their staff medium intensity: places with controlled public attendance strong intensity: places with uncontrolled crowds	
Special functions	Warning beep for imminent sanitation; Energy saving; Off Boiler in stand by	
Power supply	230 Vac / 110 Vac (optional on request)	
Heating consumption	600 W	1000 W
Maintenance consumption	60 W	60 W
Installation	Fixed to the wall	Fixed to the wall
Dispensers protection	Yes	
Status indicator	Through LED and display	
Input	Not used	
Output	Available for manual signaling	
Connections	Universal	
GSM 2 G	SANY SAFE L 2G	SANY SAFE XL 2G
GSM 4 G	SANY SAFE L 4G	SANY SAFE XL 4G
GSM included (2G/4G)	GPRS always connected with CLOUD Programming configuration parameters with APP Sany Safe Automatic time synchronization in GPRS User management with APP Sany Safe	
Sim Card	Included and active for 2 YEARS* *available for all EU countries	
Programming and user management	Via APP (Sany Safe)	
Programming by App	Environment volume Sanitization intensity Sanitization time scheduling 4 times/days sanitization time scheduling Time zone	
User management from APP	Manual activation/deactivation of sanitization Manual activation/blocking of sanitization in progress Activation/reactivation of sanitization cycle Disable sanitization for n° of days Visualization of sanitizations carried out and available Faults visualization Tank level visualization	
Dimensions (LxHxD) mm	358 x 264 x 166	480 x 353 x 166
Weight Kg.	12 Kg	18.5 Kg

N.B. SANY SAFE is not a MSD (Medical Surgical Device)