

	SANY SAFE L	SANY SAFE XL
Cover volumes	From 20 m ³ to 300 m ³	From 100 m ³ to 600 m ³
Tanks available	5 L - 10 L - 25 L	
Autonomy days of sanitation	It depends on: intensity, frequency, volume of the environment, tank capacity (8 months with: light intensity / 1 day of the week / 100 m ³ / 25 L)	
Light: 7 g/s - 100 m³	5 liters = 7 weeks	10 liters = 14 weeks
Medium: 3 g/s - 100 m³	5 liters = 6 weeks	10 liters = 11 weeks
Strong: 1g/s - 100 m³	5 liters = 5 weeks	10 liters = 10 weeks
Sanitization efficiency	low intensity: approximately 1 day medium intensity: approximately 2 days strong intensity: approximately 1 week	
Special functions	Warning beep for imminent sanitation; saving; Off Boiler in stand by	Energy
Power supply	230 Vac	
Heating consumption	600 W	1000 W
Maintenance consumption	60 W	60 W
Installation	Fixed to the wall/portable with handle	Fixed to the wall
Dispensers protection	Yes	
Status indicator	Through LED and display	
Input	Not used	
Output	Available for manual signaling	
Connections	Universal	
GSM 2 G models	SANY SAFE L 2G	SANY SAFE XL 2G
GSM 4 G models	SANY SAFE L 4G	SANY SAFE XL 4G
GSM included	GPRS always connected with CLOUD Programming configuration parameters with APP – Sany Safe Automatic time synchronization in GPRS User management with APP - Sany Safe	
Sim Card	Included and active for 2 YEARS* *available for all EU countries	
Programming and user management	Via APP (Sany Safe)	
Programming by App	Environment volume Sanitization intensity Sanitization time scheduling Days of the week to start the sanitizing cycle Time zone	
User management from APP	Manual activation of sanitization Block sanitation in progress Disable sanitization for n ° days Reactivate the sanitation cycle Tank change management Visualization of sanitizations carried out and available Visualize tank level	
Dimensions (LxHxP) mm	264 x 166 x 358	353 x 166 x 480
Weight Kg.	12 Kg	18.5 Kg

N.B. SANY SAFE is not a MSD (Medical Surgical Device)